

weberprim podloga

ACRYLIC PRIMER

weberprim podloga is a concentrated acrylic primer used for preparation of surface prior to application of paint and/or skimming compounds.

Product benefits:

- Homogenizes the absorption of the surface
- Increases adhesion
- Bonds with dust particles

Area of application

May be used with normally absorbent surfaces and is used for surface impregnation, bonding of dust, regulation of absorption and improvement of adhesion of the next layer. Intended for wall and ceiling surfaces with new and renovated old buildings.



Surface preparation

The base on which the product is applied on must be clean, solid, dry, without traces of oil and grease, supported and without parts falling off. May be applied on surfaces based on lime, plaster, cement, cement-lime plaster at least one month old, plaster cardboard panels, skimming plasters and paints. Insufficiently supported coatings and parts that are falling off, should be fully removed and repaired using appropriate material prior to primer application. Surfaces contaminated with mold should be washed with hot water and disinfected with appropriate products.

Product use and installation

1. Prior to use, dilute the primer with pure water in scale 1:8 and mix until the product is fully homogenous. Reduction or increase of scale of mixing water and concentrate is not recommended and may lead to undesired effects.
2. The surface of the facade should be coated with primer weberprim podloga minimum 12 h prior to the beginning of the application of paint or skimming mass. Primer is transparent and is not toned in Weber mix system.
3. Use a roller and/or a brush for the application of weberprim podloga. Application should be performed evenly over the entire surface, making sure there is no leaking along the surface. Uneven application shall lead to uneven absorption of the surface, which is especially sensitive with painting since it can have a negative impact on coverage and evenness of the tone and structure.
4. Drying of the primer takes at least 12h in optimum conditions. At lower temperatures and at increased humidity, the drying can last longer, while with absorbent surfaces and higher air temperature and surface temperature it can be shorter.

* All stated parameters refer to standard weather conditions: temperature 20°C, relative humidity up to 65%.

5. Temperature of the surface and air during the application of facade primer weberprim podloga must be between 5°C and 30°C. In case weather conditions do not match the requirements; it is necessary to stop the work and wait for the optimum conditions.

The manufacturer recommends application on small, test surfaces to make sure the product/surface are properly prepared and that appropriate conditions of use and installation are provided. If not, please stop the work and contact the representative of Saint-Gobain građevinski proizvodi d.o.o. Beograd. The company shall not be responsible for incorrect execution of works with the stated material as well as use of material for the purpose not stated in product description. Complaints submitted after the completion of execution of works shall not be accepted.

Tools

For mixing: electric mixer or manually.
For application: roller and/or brush.

Product consumption

Approximately 0,03-0,05 kg/m² for a layer of primer application. Consumption may differ depending on absorption and roughness of surface, type of tool, air and surface temperature, etc.

Keeping, storage and transport

Product weberprim podloga must be stored in original, undamaged packaging, on solid and functional pallets, in dry space, without direct exposure to snow, rain, hail and sun, protected from frost, in closed or covered space.

The product is not hazardous for transport in the sense of all national and international transport regulations. During transport, the product must be protected from the elements. Transport and store the product at temperature from +5°C to +30°C.

Product safety

Product not classified as hazardous.
Contains reaction mixture 5-chlorine-2-methyl-4-isothiazoline-3-on and 2-methyl-2H-isothiazole-3-on (3:1). May cause allergic reactions.

Technical characteristics of the product

Product color: weberprim podloga is transparent and is not toned as per Weber mix system.

Packaging: plastic bucket 3 kg, 288 kg on the pallet, plastic bucket 1 kg, 240 kg on the pallet.

Expiration date: 12 months from the production date pressed on the bucket.

Detailed information on product, additional documentation and safety data sheet are available on the official webpage www.rs.weber.

Cleaning

Residue of fresh product can be cleaned from the tools and surfaces with water. Hardened product must be removed only mechanically.

Product limitations

Universal primer weberprim surface cannot be used in the following situations:

- With surfaces containing moisture
- With insufficiently supported surfaces
- At temperatures for storage, transport, application and drying lower than +5°C and higher than +30°C,
- With surfaces containing algae and fungus

Environment

Unused product and empty packaging may not be disposed outside of waste management locations. See safety data sheet of the product for more information.

Disposal method

Disposal of content and packaging in line with local regulations. Dispose the packaging and unused material separately. Do not allow penetration into the sewerage system. Do not dispose together with municipal waste.

Country of origin and product manufacturer

Country of origin: Republic of Serbia

Manufacturer: Saint-Gobain građevinski proizvodi d.o.o. Beograd, 115d Bulevar Mihajla Pupina Street, 5th floor, 11070 Novi Beograd, Republic of Serbia.
Contact telephone: 011 314 96 81.



**SAINT-GOBAIN GRAĐEVINSKI
PROIZVODI D.O.O. BEOGRAD**
115d Bulevar Mihajla Pupina Street,
V floor 11070 • Novi Beograd • Serbia
Tel.: + 381 11 314 96 84
info.rs@saint-gobain.com
www.saint-gobain.rs

Technical information stated herein as well as recommendations are based on our knowledge and experience in cases when the product is properly stored, used, transported and when handled in regular conditions. The buyer, or the user of the product is advised to test the product, if it is suitable for use for intended purpose. Considering the fact, we do not have influence on the circumstances of product use and handling, we shall not be liable for consequences occurring from irregular use. The buyer, or the user of the product shall be liable in case the product is kept, transported, installed and used contrary to instructions, purpose and properties and information on product safety, as well as after stated expiration date for product use. Our team of experienced experts provides advice in phases of planning and application of our products. Visit to the construction site and demonstration of application of our products may be organized at request. Contact our technical team and find out more on our products on the website www.saint-gobain.rs.