

weberdry quartz

PURE, FACTORY
DRIED QUARTZ SAND
GRANULATION 0.1
TO 0.7MM

Area of Application

As a bonding bridge to increase adhesion when waterproofing under ceramic tiles in bathrooms, kitchens, utility rooms, etc.

As a wearing layer during the manufacturing of polyurethane and epoxy floor coverings, pedestrian, bicycle and car roads.

weberdry quartz is a pure, factory-dried quartz sand with a grain size of 0.1 to 0.7 mm that is used to create a bonding bridge or wear-resistant surface with the use of polyurethane or epoxy waterproofing coatings.

Product benefits:

- Pure factory-dried quartz sand



Product preparation and installation

1. Saturate the freshly applied waterproofing layer by sprinkling it with quartz sand weberdry quartz.
2. After drying, remove excess sand with a brush or industrial vacuum cleaner.

The manufacturer recommends, before the start of works, to perform smaller, test surfaces to check if the product/surface is properly prepared and if the appropriate conditions for use and installation have been provided. If not, please stop the work and contact the representative of Saint-Gobain građevinski proizvodi d.o.o. Beograd. The company will not be liable for irregular execution of works with stated material as well as use of material for purposes not stated in the product description. Complaints after the completed execution of works shall not be accepted.

Tools

To be applied: manually or mechanically.
To remove excess material: brush, industrial vacuum cleaner.

Product consumption

Product consumption: from 1.0 to 3.5 kg/m²/mm.
The consumption is approximate and given based on the saturation of the waterproofing layer with a thickness of 1 mm.

Keeping, storage and transport

The product must be stored in its original, undamaged packaging, in a dry and closed space, protected from the elements.

The product is not hazardous for transport in the sense of all national and international transport regulations. During transport, the product must be protected from the elements.

Product safety

Product is not classified as hazardous.

Technical characteristics of the product

Product color: brown.

Packaging: 25 kg sack.

Useful life: unlimited.

Factors such as temperature and method of application may significantly affect consumption.

Detailed information on the product, additional documentation and safety data sheet, are available www.rs.weber.

Granulometric composition

SIEVE OPENING, MM	RESIDUE ON THE SIEVE, %
1.0	max 1.0
0.71	max 15.0
0.50	30.0 – 50.0
0.355	35.0 – 55.0
0.25	max 10.0
0.18	max 1.0
0.125	max 0.1
0.09	-
0.063	-
bottom	-
Average grain size, mm	0.45 - 0.55
Degree of evenness, %	min. 80
Grain fineness number	25 - 35

Environment

Unused product and empty packaging may not be disposed outside of waste management locations.

Disposal method

Disposal of content and packaging in line with local regulations. Dispose the packaging and unused material separately. Do not allow penetration into the sewerage system. Do not dispose together with municipal waste.

Country of origin and product manufacturer

Country of origin: Republic of Serbia.

Manufacturer: Saint-Gobain građevinski proizvodi d.o.o. Beograd, 115d Bulevar Mihajla Pupina Street, 5th floor, 11070 Novi Beograd, Republic of Serbia.
Contact telephone: 011/3149681.



**SAINT-GOBAIN GRAĐEVINSKI
PROIZVODI D.O.O. BEOGRAD**
115d Bulevar Mihajla Pupina Street,
V floor 11070 • Novi Beograd • Serbia
Tel.: + 381 11 314 96 84
info.rs@saint-gobain.com
www.saint-gobain.rs

Technical information stated herein as well as recommendations are based on our knowledge and experience in cases when the product is properly stored, used, transported and when handled in regular conditions. The buyer, or the user of the product is advised to test the product, if it is suitable for use for intended purpose. Considering the fact, we do not have influence on the circumstances of product use and handling, we shall not be liable for consequences occurring from irregular use. The buyer, or the user of the product shall be liable in case the product is kept, transported, installed and used contrary to instructions, purpose and properties and information on product safety, as well as after stated expiration date for product use. Our team of experienced experts provides advice in phases of planning and application of our products. Visit to the construction site and demonstration of application of our products may be organized at request. Contact our technical team and find out more on our products on the website www.saint-gobain.rs.