

weberton bet

ACRYLIC DISPERSION CONCRETE PAINT

weberton bet is a facade dispersion paint based on high-quality acrylic emulsion. Owing to selected polymers and additives it is persistent over a long period of time and resistant to all weather conditions.

Product benefits:

- Good flexibility
- Great coverage
- UV resistance

Product classification:

G₃-E₃-S₁-V₂-W₂ (EN 1062-1:2004)

Area of Application

It is persistent over a prolonged period of time, characterized by high water resistance and resistance to all weather conditions. It is not intended for high mechanical load such as pedestrian or road traffic. May be used with renovation of old, as well as painting of new buildings.



Surface preparation

Surface on which the product is applied must be clean, solid, dry, without traces of grease and oil, and without parts falling off. Weberton bet may be applied on surfaces based on cement. Cement plasters and concretes must be at least one month old, with moisture residue equal or less than 1,5%. Coatings with low support and parts that are falling off, coatings that are water soluble (during surface washing) should be fully removed and repaired with appropriate material prior to primer application. Surfaces contaminated with mold and algae should be washed with hot water and disinfected with appropriate products.

Appropriate surface prior to application of the facade paint is the weberprim surface, that is diluted with pure water in ratio 1:8. Old cement surfaces should be covered with weberprim deep primer diluted with pure water in ratio 1:6, at least 12 h prior to application of facade paint.

Product use and installation

1. Prior to the start of works it is necessary to properly mix the concrete paint to the bottom of the bucket and afterwards homogenous material from different lots and/or packages in one large vessel for tone harmonization (equalizing). Add up to 10% of pure water during dilution, to get required material consistency.
2. Apply weberton bet on the prepared surface with roller or brush in at least two layers, in order to achieve full coverage of the surface and get the required paint tone. Application should be done consistently and in continuity, in order to achieve consistency of the and consistent drying. Apply the second layer only after the first layer is fully dry, that is, 6 h, at the earliest from the application of the first layer at optimum weather conditions. Product is not intended for horizontal treading surfaces due to possibility of wiping.

3. During installation and drying the temperature of the surface and air must be between 5°C and 30°C. Material should be protected from the sun, wind, fog and rain for at least 24h, after which resistance is achieved to atmospheric impact. Recommended method of protection is setting scaffold screens, but this could be insufficient if stated impact is of strong intensity. In case weather conditions do not comply with the stated, it is necessary to stop the work and wait for the optimum conditions.

*All stated parameters refer to standard weather conditions: temperature 20°C, relative humidity up to 65%.

4. It is recommended to regularly maintain the painted facade surface, by de-dusting the layers of dust and by removing traces of dirt using hot water and/or cleaning products. Regular maintenance shall reduce the possibility for the occurrence of algae, fungus and extends the useful life of painted surfaces.

The manufacturer recommends, before the start of works, to perform smaller, test surfaces to check if the product/surface is properly prepared and if the appropriate conditions for use and installation have been provided. If not, please stop the work and contact the representative of Saint-Gobain građevinski proizvodi d.o.o. Beograd. The company will not be liable for irregular execution of works with stated material as well as use of material for purposes not stated in the product description. Complaints after the completed execution of works shall not be accepted.

Tools

For mixing: electric mixer or manually.
For application: roller and/or brush.

Product consumption

Approximately 0,2-0,4 kg/m² for two layers of facade acrylic paint, depending on layer thickness, surface absorption and conditions in which wall painting is performed.

Keeping, storage and transport

Weberton bet must be stored in original, undamaged packaging, on solid and functional pallets, in dry space, without direct exposure to snow, rain, hail and sun, protected from frost, in closed or covered space.

The product is not hazardous for transport in the sense of all national and international transport regulations. During transport, the product must be protected from the elements. Product should be transported and stored at temperature from +5°C to +30°C.

Product safety

Product not classified as hazardous.
Contains reaction mixture 5-chlorine-2-methyl-4-isothiazoline-3-on and 2-methyl-2H-isothiazole-3-on (3:1). May cause allergic reactions.

Technical characteristics of the product

Product color: weberton bet is an acrylic white paint (available in almost 9 tones in line with Weber tone card).

Packages: plastic bucket 5 kg, 480 kg on the pallet; plastic bucket 1 kg, 288 on the pallet;
Expiration date: 12 months from the production date pressed on the bucket.

Detailed information on the product, additional documentation and safety data sheet, are available on the official webpage www.rs.weber..

Cleaning

Residue of fresh product can be cleaned from the tools and surfaces with water. Solid products may be removed only mechanically.

Product limitations

Concrete paint weberton bet cannot be used in the following situations:

- With wall surfaces containing moisture
- With old and insufficiently supported surfaces
- At temperatures lower than +5°C and higher than +30°C
- With surfaces containing algae and fungus

Environment

Unused product and empty packages cannot be disposed of outside of dedicated locations. See safety data sheet of the product for more information.

Disposal method

Disposal of content and packaging in line with local regulations. Dispose the packaging and unused material separately. Do not allow penetration into the sewerage system. Do not dispose together with municipal waste.

Country of origin and product manufacturer

Country of origin: Republic of Serbia

Manufacturer: Saint-Gobain građevinski proizvodi d.o.o. Beograd, 115d Bulevar Mihajla Pupina Street, 5th floor, 11070 Novi Beograd, Republic of Serbia.
Contact telephone: 011 314 96 81.



**SAINT-GOBAIN GRAĐEVINSKI
PROIZVODI D.O.O. BEOGRAD**
115d Bulevar Mihajla Pupina Street,
V floor 11070 • Novi Beograd • Serbia
Tel.: + 381 11 314 96 84
info.rs@saint-gobain.com
www.saint-gobain.rs

Technical information stated herein as well as recommendations are based on our knowledge and experience in cases when the product is properly stored, used, transported and when handled in regular conditions. The buyer, or the user of the product is advised to test the product, if it is suitable for use for intended purpose. Considering the fact, we do not have influence on the circumstances of product use and handling, we shall not be liable for consequences occurring from irregular use. The buyer, or the user of the product shall be liable in case the product is kept, transported, installed and used contrary to instructions, purpose and properties and information on product safety, as well as after stated expiration date for product use. Our team of experienced experts provides advice in phases of planning and application of our products. Visit to the construction site and demonstration of application of our products may be organized at request. Contact our technical team and find out more on our products on the website www.saint-gobain.rs.