

weberfloor parketofix

SINGLE-COMPONENT
WATER-BASED PARQUET
ADHESIVE

weberfloor parketofix is a single-component, dispersive, water-based, toluene-free parquet adhesive for gluing parquet in the interior.

Product benefits:

- Economical solution
- Good adhesion
- Water-based

Area of application

weberfloor parketofix is used for gluing laminate and classic parquet of smaller dimensions on stable cement and other absorbent substrates with good load-bearing capacity in interiors.



Surface preparation

The base whereon the product is applied on must be clean, solid, dry, supported and without parts falling off. All materials that reduce adhesion (paint residue, plaster, grease, dust, etc.) should be fully removed. Surface tensile strength of the surface measured by "pull off" test must be $> 1.0 \text{ N/mm}^2$.

Concrete surfaces and cement screeds (old min. 28 days with moisture residue $\leq 2\%$), must be mechanically roughened and dust-free, and then coated with a suitable primer. Coat absorbent and old surfaces with weberprim deep primer at least six hours before starting work (at an optimum temperature of 20°C , relative humidity up to 65%).

Product use and installation

1. If necessary, mix the adhesive with an electric mixer.
2. Apply the adhesive with a notched trowel, install the parquet and press.
3. Wait for 24 hours and continue with sanding and varnishing.

*All stated parameters refer to standard weather conditions: temperature 20°C , relative humidity up to 65% . If the weather conditions are not in line with standard it is necessary to adjust the process to the given circumstances and expect the product will bond quicker in warmer weather, i.e. lower in the cold, making sure the temperature of the surface and air is in the range from 5°C to 30°C .

The manufacturer recommends application on small, test surfaces to make sure the product/surfaces are properly prepared and whether appropriate conditions for use and installation have been provided. If not, please stop the work and contact the Saint-Gobain građevinski proizvodi d.o.o Beograd.

The company shall not be responsible for incorrect execution of works with the stated material as well as use of material for the purpose not stated in product description. Complaints submitted after the completion of execution of works shall not be accepted.

Tools

For mixing: electric mixer.
For application: trowel.

Product consumption

Product consumption: from 0.9 to 1.2 kg/m^2 , depending on the characteristics of the surface.

Keeping, storage and transport

Product must be stored in original, undamaged packaging, in dry and closed space, protected from elements.

The product is not hazardous for transport in the sense of all national and international transport regulations. During transport, the product must be protected from the elements. Transport and store the product at temperature from $+5^\circ\text{C}$ to $+30^\circ\text{C}$.

Product safety

Product not classified as hazardous. Contains reaction mixture 5-chlorine-2-methyl-4-isothiazoline-3-on and 2-methyl-2H-isothiazole-3-on (3:1). May cause allergic reactions.

Technical characteristics of the product

Product color: brown.

Open work time: approximately 30 minutes depending on weather conditions and thickness of the layer.

Packaging: 25 kg bucket, 600 kg on a pallet

Expiration date: 12 months from the production date pressed on the packaging.

Detailed information on product, additional documentation and safety data sheet are available on the official webpage www.rs.weber.

Cleaning

Residue of fresh product can be cleaned from the tools and surfaces with water. Dry product may be removed mechanically.

Product limitations

weberfloor parketofix cannot be used in the following situations:

- With insufficiently supported surfaces
- At temperatures lower than +5°C and higher than +30°C.
- With surfaces containing impurities and water.

Environment

Unused product and empty packaging may not be disposed outside of waste management locations. See safety data sheet of the product for more information.

Disposal method

Disposal of content and packaging in line with local regulations. Dispose the packaging and unused material separately. Do not allow penetration into the sewerage system. Do not dispose together with municipal waste.

Country of origin and product manufacturer

Country of origin: Republic of Serbia

Manufacturer: Saint-Gobain građevinski proizvodi d.o.o. Beograd, 115d Bulevar Mihajla Pupina Street, 5th floor, 11070 Novi Beograd, Republic of Serbia. Contact telephone: 011 314 96 81.



**SAINT-GOBAIN GRAĐEVINSKI
PROIZVODI D.O.O. BEOGRAD**
115d Bulevar Mihajla Pupina Street,
V floor 11070 • Novi Beograd • Serbia
Tel.: + 381 11 314 96 84
info.rs@saint-gobain.com
www.saint-gobain.rs

Technical information stated herein as well as recommendations are based on our knowledge and experience in cases when the product is properly stored, used, transported and when handled in regular conditions. The buyer, or the user of the product is advised to test the product, if it is suitable for use for intended purpose. Considering the fact, we do not have influence on the circumstances of product use and handling, we shall not be liable for consequences occurring from irregular use. The buyer, or the user of the product shall be liable in case the product is kept, transported, installed and used contrary to instructions, purpose and properties and information on product safety, as well as after stated expiration date for product use. Our team of experienced experts provides advice in phases of planning and application of our products. Visit to the construction site and demonstration of application of our products may be organized at request. Contact our technical team and find out more on our products on the website www.saint-gobain.rs.